

ZIP HYDROTAP G4 BC 100/75

Order Code HT1764

Zip HydroTap Boiling, Chilled, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	2824AU0H0ZN1C
Capacity	Commercial
Disability Options	Available
Boiling Cups per hour	100
Chilled Cups per hour	75



Тар	Zip HydroTap CLASSIC Tap (Chrome)				
Water Pressure	Min 172kPa - Max 700kPa				
Water Connection	12.7mm BSP				
Water Supply Requirements	Cold				
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Rating	2.05kW 220-240V 50Hz				
Power Supply	1 x 10Amp GP0				
Dimensions	H333mm x W280mm x D455mm				
Product Approvals	WaterMark, CE, RCM, ARC				
Warranty	2 years				

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.

- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

