

## ZIP HYDROTAP G4 ALL-IN-ONE BCSHA 240/175

## Order Code HT1772

Zip HydroTap All-in-One Boiling, Chilled, Sparkling, Filtered water plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark", 0.2 micron water filtration and a refillable CO2 cylinder.

Manufacturing Code	5353AU0A6ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	240
Combined Chilled and Sparkling Cups per hour	175



Тар	Zip All-in-One CLASSIC Tap (Chrome)			
Water Pressure	Min 250kPa - Max 700kPa			
Water Connection	12.7mm BSP			
Water Supply Requirements	Cold			
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve			
Power Rating	2.3kW 220-240V 50/ 60Hz			
Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz			
Power Supply	2 x 10Amp GPO's (or 1 x 10Amp Double GPO)			
Dimensions	H333mm x W394mm x D464mm			
Product Approvals	WaterMark, CE, RCM, ARC			
Wels Rating	5 Star, 5 litres			
Warranty	2 years			

## Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

## Installation Detail

