

## ZIP HYDROTAP CELSIUS ARC CS

## Order Code MT2787

Zip HydroTap Design Range CELSIUS Chilled and Sparkling Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 0.2 micron water filtration and 2 disposable CO2 cylinders.

Manufacturing Code	0056AU0C4ZN1R
Capacity	Residential
Disability Options	Unavailable



Тар	Zip HydroTap Design Range CELSIUS ARC Tap (Chrome)				
Water Pressure	Min 250kPa - Max 700kPa				
Water Connection	12.7mm BSP				
Water Supply Requirements	Cold and Hot				
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Rating	0.35kW 220-240V 50Hz				
Power Supply	1 x 10Amp GPO				
Dimensions	H333mm x W280mm x D405mm				
Product Approvals	WaterMark, CE, RCM, ARC				
Wels Rating	5 Star, 5.5 litres				
Warranty	2 years				

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

## **Installation Detail**

