



ZIP HYDROTAP CELSIUS CUBE CS

Order Code MT3787

Zip HydroTap Design Range CELSIUS Chilled and Sparkling Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	0054AU0C5ZN1R
Capacity	Residential
Disability Options	Unavailable



Tap	Zip HydroTap Design Range CELSIUS CUBE Tap (Chrome)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold and Hot
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.35kW 220-240V 50Hz
Power Supply	1 x 10Amp GPO
Dimensions	H333mm x W280mm x D405mm
Product Approvals	WaterMark, CE, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	2 years

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail



