

ZIP HYDROTAP CELSIUS CUBE C

Order Code MT3888

Zip HydroTap Design Range CELSIUS Chilled Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection and 0.2 micron water filtration.

Manufacturing Code	0015AU0C3ZN1R
Capacity	Residential
Disability Options	Unavailable



Тар	Zip HydroTap Design Range CELSIUS CUBE Tap (Chrome)				
Water Pressure	Min 172kPa - Max 700kPa				
Water Connection	12.7mm BSP				
Water Supply Requirements	Cold and Hot				
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Rating	0.125kW 220-240V 50Hz				
Power Supply	1 x 10Amp GP0				
Dimensions	H333mm x W280mm x D405mm				
Product Approvals	WaterMark, CE, RCM, ARC				
Wels Rating	5 Star, 5.5 litres				
Warranty	2 years				

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

